



## Fire sleeve - F88 SC · Model DK

Silicone-coated fire sleeve with snap fastener for subsequent assembly.

### Technical data

**Source material**

Fire sleeve F88 SC

**Fastening**

Snap fastener made of brass, nickel-plated  
dimensions 15 mm diameter, height 3 mm  
distance between hook-and-loop fasteners: 80 mm

**Technical values**

Kevlar® strips type KV290 to prevent thermal  
bridges on metal fasteners  
as well as edge protection

**Available sizes**

Available lengths on demand, maximum 25 m  
not a stock item; delivery time after consultation

**Key characteristics**

- excellent mechanical protection
- halogen-free flame protection
- free of softeners
- free of heavy metals
- REACH-compliant

### Product details

DN	product number	approx. weight g/m
30	4499 9 030	580
40	4499 9 040	675
50	4499 9 050	775
60	4499 9 060	870
70	4499 9 070	990
80	4499 9 080	1100
90	4499 9 090	1195
100	4499 9 100	1290
110	4499 9 110	1390
120	4499 9 120	1500

DN	product number	approx. weight g/m
130	4499 9 130	1610
140	4499 9 140	1690
150	4499 9 150	1810
160	4499 9 160	1910
170	4499 9 170	2005
180	4499 9 180	2105
190	4499 9 190	2220
200	4499 9 200	2330
220	4499 9 220	2520
250	4499 9 250	2815

Status as of 05/2023 · Technical changes in the course of development reserved.

